

WSK060_Sannibire_Silencing_Machine



厚度 Specification	5mmes (max)
長度 Length	2000mm
厚度 Thickness	>0.2mm

主要参考文献

号轮直径 Guide wheel diameter	220mm
号轮轴距 Guide wheel base	440mm
号轮长度 Guide wheel length	266mm
号轮重量 Guide wheel weight	5.00kg (11.02lb)
送料速度 Feeding rate	0.01mm-2.00mm/min
摇摆角度 Swinging angle	±12°
切割方向 Cutting direction	forward or reverse cutting (right or left)
存储线盘 Storage wire diameter	3.0mm
送料速度 Feeding rate	2200L/min

能源经济 power economy

电源选择 power connection	220V/380V, 3PH, 50/60Hz
额定功率 rated power	35kW
冷却方式 Cooling/Water/water	12~17℃

外形尺寸 outline size

机床重量 weight	1200kg
-------------	--------

小區區長張榮德...

设备用途与注意事项

- 采用进口石英制钢线夹，切割速度达到100mm/s，切割精度达到±0.01mm
- 割硅、锗、石英玻璃、陶瓷、蓝宝石晶体等。
- 机床所有电器元件均采用国际知名品牌，保证机床的稳定性。
- 采用进口了控制技术的，日本DCMP，控制精度高。
- 电控柜配备独立温控系统，保证设备，温度在15-25℃。
- 设备具备摆动功能，可支撑锯片上下摆动，可全副线切割的精度，功能，缩短了切割时间，并提高了晶片的产量。
- 滑轮数量最少化设计（仅3个滑轮），减少侧偏和振动故障。

Aplicații de testare

- This machine is used for automatic diamond grinding, grinding, honing and cutting materials, diamond grinding tools for diamond, germanium, silicon, sapphire, ceramics, sapphire crystals, etc.
- All steel and cast iron parts, quality mechanical and electrical processing brands to ensure the stability of the machine
- Apply integrated PLC or SIEMENS motion controlling system, 15.6" touch screen control
- The electric control cabinet has a built-in air conditioning system to ensure the control system to ensure the normal operation of the control system
- The equipment has a built-in automatic lubrication system, the automatic lubrication function unit optimizes the performance of the machine, and the automatic lubrication system ensures the cooling time and reduces the wear of the machine
- Minimal design, symmetrical design, symmetrical, non-symmetrical, reduce the vibration and fatigue

